

FITTING GUIDE FOR VINYL DOOR SIGNS

GENERIC INSTRUCTIONS FOR DRY APPLICATION METHOD TO FIX TO CLEAN, DRY SURFACES ON THE VEHICLE

Recommended materials required: Clean, soft, lint-free cloth and your door sign.

Prep: Ensure the intended area for fitting is clean and dry - avoid polish prior to fitting.



Designated Position of Door Signs:

Make sure your vinyl self adhesive door sign is positioned as specified by your Local Authority Licensing Department.

THESE SIGNS MUST BE ATTACHED DIRECTLY TO THE VEHICLE AND ONLY IN ACCORDANCE WITH THESE GUIDELINES.

First choose the correct area by offering the door sign up to the designated central position on the front doors. Now, thoroughly clean and dry the surface where the sign is to be applied using a clean and dry lint-free cloth.



Peel off a small segment of the backing paper from one end of the door sign, and fold over to expose a portion of adhesive on the rear of the printed door sign. Now you have formed a 'hinge'.



Align your sign accurately and apply the exposed portion of the adhesive area on the rear of the sign directly to the door. Now slowly from the 'hinged' area which is now attached to the vehicle, pull off the remainder of the backing paper and smooth down the sign firmly and evenly with a soft cloth. Take care to expel all the air as you go by applying pressure from the centre of the sign outwards.



Finally smooth over the sign with a soft cloth, applying pressure. Any small air bubbles may be gently pushed with the tip of your finger and expelled by applying pressure. Please note that these industry standard vinyl materials will take a number of hours to achieve maximum adhesion to the surface of the vehicle. We do not recommend washing the area within 48 hours of installation.



CARE AND MAINTENANCE OF DOOR SIGNS

Normal car washing with non-aggressive detergents will keep door signs in prime condition. Wax based products such as 'Turtle Wax' may also be used. DO NOT USE aggressive or solvent based products such as T-CUT or AutoGlym paint restorers as these products are designed to remove the top layer of paint.

REMOVAL OF DOOR SIGNS

Ensuring that the sign remains in one piece gently peel off from the outside edge and keeping door sign taut pull away from vehicle. Following removal of the sign, clean off any adhesive residue remaining on the vehicle with soapy water. Finally wipe down the surface again with a clean, soft cloth leaving paintwork clean and dry. Applying gentle heat with a hairdryer may be helpful if required.

Disclaimer: the supplier NewAuto Limited trading as Mogo UK (and any associated company) has no control over how signs are cared for, altered, stored, affixed and/or used, or over the surface to which they are applied. As a result, NewAuto Limited trading as Mogo UK (and any associated company) accepts no liability whatsoever, in any circumstances, for any claim or claims for alleged loss or damage relating to the use of, application or removal of the signs supplied. NewAuto Limited is unable to enter any dialogue with the 'trade' on this subject. The purchaser and/or user will be deemed to accept this disclaimer in the use of these products.